



# nyloflex® Cutting Table FIV

## Equipment Dimensions

Technical data	nyloflex® Cutting Table FIV
Dimensions (L x W x H)(mm inch)	2100mm x 1000mm x 940mm (82.7" x 39.8" x 37.0")
Maximum cutting width	1600 mm (62.9")
Maximum cutting thickness	7 mm (0.28")
Electrical connection	230 V, 50/60 Hz (1 Ph/N/PE)
Nominal current	1 A
Nominal power	0.2 kW
Compressed air	male coupling, 7.2 mm, 8-10 bar (0.28", 116 - 145 PSI)
Weight (approx.)	260 kg (574 lbs) net 580 kg (1279 lbs) gross
Crate dimensions (L x W x H)(mm inch)	2400mm x 1250mm x 1650mm (94.5" x 49.2" x 65.0")

**Please contact us for additional information.**

info@xsyglobal.com • www.xsyglobal.com

The aim of our technical documents is to inform and advise our customers. The information provided herein is correct to the best of XSYS's knowledge. No liability for any errors, facts or opinions is accepted. Customers must satisfy themselves as to the suitability of this product for their application. No responsibility for any loss as a result of any person placing reliance on any material contained herein will be accepted. Product names followed by ® are trademarks registered by XSYS Germany GmbH and/or its affiliates.



**XSYS** 04-2023  
Print solid. Stay flexible.