

XSYS

Print solid. Stay flexible.

nyloflex[®] Cutting Table F IV

Cutting table designed for
cutting foil based photopolymer
printing plates



Be
brilliant.

PRODUCT FEATURES

- **Clean and smooth** plate cutting.
- **Robust and easy** to maintain.
- **Simple** to operate.
- **Optimum** productivity.
- **The photopolymer plates can be cut** at any angle between 0° to 40°. The cutting speed is adjustable between the range of 1 to 11 m/min to accommodate for the thickness or type of plate being cut.



EASY AND COMFORTABLE HANDLING

- **Clamp opening up to 8 mm** (0.31") provides space to easily manoeuvre all plate thicknesses.
- **Two-handed** operation for optimum safety.
- **Illuminated cutting channel** allows precise positioning and cutting of the plate.
- **Easy maintenance** with quick replacement of the cutting blade.



EXCELLENT QUALITY AND CONSISTENCY

- **Cutting width of 1600 mm** (62.0") - suitable for plates up to 1600 mm.
- **Fast, precise and safe** cutting of polyester foil based plates with clean burr-free edges.
- **Cutting blade and clamp** are operated by compressed air.



nyloflex® Cutting Table F IV

Wide web format, suitable for processing high quality photopolymer plates up to a maximum of 1600 mm (62 inch) and up to a thickness of 7 mm (0.275 inch).

Be
brilliant.

nyloflex®

Cutting Table F IV

Cutting table designed for cutting foil based photopolymer printing plates

Technical data	nyloflex® Cutting Table F IV
Maximum cutting width	1600 mm (62.9")
Maximum cutting thickness	7 mm (0.28")
Electrical connection	230 V, 50/60 Hz (1 Ph/N/PE)
Nominal current	1 A
Nominal power	0.2 kW
Compressed air	male coupling, 7.2 mm, 8-10 bar (0.28", 116 - 145 PSI)
Weight (approx.)	260 kg (574 lbs) net 580 kg (1279 lbs) gross
Crate dimensions (W x D x H)	2400 mm x 1250 mm x 1650 mm (94.5" x 49.2" x 65.0")

Please contact us for additional information.

info@xsyglobal.com • www.xsyglobal.com

Our technical documents are designed to inform and guide our customers. The information provided herein is accurate to the best of XSYS's knowledge; however, we accept no liability for any errors, inaccuracies, or opinions expressed. Customers are responsible for determining the suitability of this product for their specific application. XSYS assumes no responsibility for any loss incurred as a result of reliance on the information contained in this document. Product names followed by ® are registered trademarks of XSYS Germany GmbH and/or its affiliates.

XSYS 03-2025

Print solid. Stay flexible.

XSYS

Print solid. Stay flexible.