

XSYS

Print solid. Stay flexible.

nyloflex[®] XPH

The thermal standard in flexo printing with water based inks



Be
brilliant.

CONSISTENT PRINT QUALITY

- **Sharp reproduction of finest elements**, screens, text and fine line work.
- **Outstanding quality** reproduction of smooth vignettes and high contrast images.
- **Excellent storage properties** and increased number of usages due to low surface tack.



APPLICATIONS

- Coated Paper.
- Aseptics.
- Narrow Web.



nyloflex[®] XPH

- High durometer flexo plate designed for excellent print quality.
- Developed for water based inks, also suitable for a broad range of UV and solvent based inks.⁴
- For printing on aseptic packaging (beverage packaging) and corrugated preprint.
- Also for labels and flexible packaging. Especially suitable for paper and rough substrates.



**ENSURES COLOR
CONSISTENCY
OF YOUR BRAND
ON THE SHELF**



**Be
brilliant.**

nyloflex® XPH Digital

The thermal standard in flexo printing with water based inks



Technical characteristics	nyloflex® XPH 114 Digital	nyloflex® XPH 170 Digital
Colour of raw plate	light blue	light blue
Total thickness (mm) ¹	1.14	1.70
Hardness acc. to DIN 53505	60	60
Plate hardness (Shore A)	77	69
Recommended relief depth (mm)	0.46 - 0.56	0.46 - 0.56
Tonal range (%)	1 - 99	1 - 99
at screen ruling (L/cm)	80	80
Fine line width - down to µm	100	100
Isolated dot diameter - down to µm	200	200

Processing parameters²

Back exposure (s)	12 - 20	40 - 50
Main exposure (min)	6 - 8	6 - 8
Post exposure UV-A (min)	10	10
Light finishing UV-C (min) ³	6-10	6-10

Processing information

Suitable equipment

nyloflex® XPH Digital plates may be exposed using any nyloflex® exposure system and all similar devices and can be used with all laser systems suitable for imaging flexo printing plates. nyloflex® XPH Digital plates must be processed with the nyloflex® Xpress Thermal Processor.

Printing inks

Suitable for all UV inks⁴ and water based printing inks.

Processing information

A detailed description of the imaging, exposure and finishing steps, as well as detailed information about handling and storing, can be found in the nyloflex® User Guide.

Certification

XSYS printing plates are produced at Willstätt production site, which is certified according to international standards for quality management (DIN EN ISO 9001:2015), environmental management (DIN EN ISO14001:2015) and energy management (DIN EN ISO 50001:2018).

1) Standard thicknesses currently available – subject to change 2) All processing parameters depend on, among other things, the processing equipment, lamp age and the type of washout solvent. A minimum exposure intensity of $\geq 17 \text{ mW/cm}^2$ is recommended. The above mentioned processing times were established under optimum conditions in our technical center. The standard test file with 149lpi was imaged at 4000DPI using a ThermoFlexX imager, 20 mW/cm^2 bank exposure, using nylosolv® A washout solvent and nyloflex® and ThermoFlexX Catena plate processing equipment. Under other conditions the processing times can differ from these; therefore, the above mentioned values are only to be used as a guide. 3) Depending on longevity of the tubes. 4) Suitability with UV inks is dependant on the ink type and temperature – these factors could affect the performance of the plate and consistency of the print.

Please contact us for additional information.

info@xsysglobal.com • www.xsysglobal.com

Our technical documents are designed to inform and guide our customers. The information provided herein is accurate to the best of XSYS's knowledge; however, we accept no liability for any errors, inaccuracies, or opinions expressed. Customers are responsible for determining the suitability of this product for their specific application. XSYS assumes no responsibility for any loss incurred as a result of reliance on the information contained in this document. Product names followed by ® are registered trademarks of XSYS Germany GmbH and/or its affiliates.

XSYS 02-2025

Print solid. Stay flexible.

XSYS

Print solid. Stay flexible.